

Industry Panel Computer, Aladdin Family

ALAD-K1820T(P)

18.5" TFT LCD, Capacitive Touch, Intel® Skylake-U CPU, 2*LAN, 4*USB3.0

ALAD-K1820T(P)




Key Feature

- Aluminum die-casting chassis, fanless design
- 18.5" LED TFT LCD, capacitive touch
- Intel® Skylake-U Core I3/I5/I7 CPU
- 1*DDR4 2133 SODIMM, Max 16GB
- 1*Mini PCIe (PCIe+ USB)
- 2*COM, 2*LAN, 4*USB3.0, 1*USB2.0
- 2.5" HDD Bay, 1*M.2
- ATX button&remote button
- DC 9~36V power input



Dimension

Unit : mm



SPEC.

System	CPU	Intel® Skylake Core I3-6100U 2.3GHz, 2C4T, TDP 15W(Optional 3855U, I5-6200U,I7-6500U)
	Chipset	Intel® SOC
	System Memory	1*DDR4 2133 MHz SODIMM, Max 16GB
	BIOS	Insyde SPI 64Mbit flash
	Storage	1*2.5" SATA HDD bay, support SATA3.0 6Gbps HDD/SSD, 1*M.2 (2242 B-Key)
	Display	18.5" LED backlight TFT LCD and HDMI (4K resolution), dual display, Intel® HD Graphics
	Touch	Projected capacitive touch, USB control
	Expansion	1*Mini PCIe(PCIe&USB signal)
	Real I/O	2*COM: 2*RS232/422/485, DB9
		4*USB3.0 Type A
		1*HDMI
		2*RJ45
	Front I/O	1*USB2.0 Type A
	LAN	Intel® I210AT chip, 10/100/1000 Mbps
	Control SW	Power button, 2-pin connector with power switch signal
Power Supply	DC to DC: 9~36V input, consumption: TDP 12V/3.72A(Intel® I5-6200U CPU, 4GB DDR3L memory)	
OS Supply	Windows 7, Windows 8.1, Windows 10, Linux	
Mechanical	Construction	Aluminum die-casting front bezel and chassis, fin-shaped radiator shell
	Operating Temperature	0~50°C -HDD(-10~55°C -SSD), with airflow
	Storage Temperature	-20~60°C
	Storage Humidity	10~95%@40°C, non-condensing
	Shock	10g peak acceleration(duration 11ms), in operating with HDD
& Environmental	Vibration	1g 5~500Hz, in operating with HDD
	Mounting	Panel mounting, VESA 100*100
	Dimension	(W*H*D):482.3*304.3*59.1mm; mounting cut out(W*H): 473.5*295.5mm
	Net Weight	6.63 KG
EMC	CE,FCC Class A	

LCD	Type	18.5" TFT LED
	Resolution	1366*768
	Color	16.7M colors
	Pixel Pitch(mm)	0.300*0.300
	Brightness(cd/m2)	300
	Viewing Angle	85 Degree(left), 85 Degree(right), 80 Degree(up), 80 Degree(down)
	Operating Temperature	-10~50°C
Touch	Backlight Lifetime	50,000 hours
	Type	Projected capacitive touch
	Resolution	gapless
	Light Transmittance	90%
	Interface	USB
	Consumption	+ 5V @ 300mA
	OS	Windows/Linux
Click Lifetime	3 billion times	

Ordering Info.

Model NO.	CPU	TOUCH	Description
ALAD-K1820T(P)/ T001	Intel® Core I3-6100U	projected capacitive touch	Industry panel computer, 18.5" TFT LCD,
ALAD-K1820T(P)/ T002	Intel® Core I5-6200U	projected capacitive touch	HDMI, 2*COM(2*RS232/422/485),
ALAD-K1820T(P)/ T003	Intel® Core I7-6500U	projected capacitive touch	5*USB, 2*LAN, 1*Mini PCIe, 2*3W speaker,
ALAD-K1820T(P)/ T004	Intel® Celeron 3855U	projected capacitive touch	1*2.5" SATA Bay, 1*M.2, DC 9~36 power input.

PA-60DC12	AC/DC power adapter, DC12V/5A 60W
-----------	-----------------------------------